TIP CERT

83-669557

CRYPTOGRAPHIC DESCRIPTION

TYPE X MACHINE

1. 14 inserts (reversible) lettered A - N and AR - NR (28 inserts in all).


- 2. 7 hollow drums with:
 - a. Moveable Tyre.
 - b. Notched rim (4 notches spaced 7-6-7-6).
- 5. 7 inserts used for limited period of time.
 - a. 5 drums with proper inserts for period used daily (RO).
 - b. Tyre setting changed daily.
- 4. 2 drums on Right Never step (E.P.).
- 5. Pluggable RW. Cannot be set.
- 6. 5 drums of cipher unit (to left) step as M-325; (cycle of machine 4,394).
 - 7. Example of daily R.C. and rim settings:

1 9 X 4 E


Rotor # 42571

Rim Setting RMV 8 0

8. Encipherment.







•	19 JANUAY 1944		2Ø JANUARY 1944	•	21 JANUA	RY_1944
w.o. 87 83	3 88 81 84R	w.o. 89R	87 82 83 88	w.o. 8ø 8	3r 85r 86r	81R
TTVXS	STEPPED TO: T S U X S 338TH: T S U X A 676TH: T S U X	PLNDB	STEPPED TO: PLMCA 338TH: PLMCU 676TH: PLMCO	RQLDV	STEPPED TO: 338TH: 676TH:	QQMEV SQMER UQME'N
QCYRF	STEPPED TO: PCXRG 338TH: PCXRO 676TH: PCXRW	YTDJH	STEPPED TO: YTCJG 338TH: YTCJA 676TH: YTCJU	SPWRN	STEPPED TO: 338TH: - 676TH:	SPXRO UPXRS WPXRW

.1-4

88 - mildle

1-4

1